



Technical Information	
Regulator	CSR485 OPSO
Capacity kg/h (kW)	4 (55)
Set Pressure	37 mbar
OPSO Set Pressure	125 mbar
UPSO Pressure	N/A
Limited Relief Valve	75 mbar
Design Standard	EN16129
Inlet connection	UK POL
Outlet connection	1/2" BSPT F

Meets current COP32 installation standards when fitted with stainless steel pigtails



- "Push to Set" CSR OPSO safety protection with consumer resettable design.
- Visible OPSO trip indicator.
- 4kg/h (55KW/h) capacity.
- Protected breather vents and tough, weatherproof ABS plastic casing
- Engineer adjustable pressure.
- Available in a range of kits, with rubber pigtails and Clessinox outlet hoses.

Part Code	Description
0485101	CSR485 Single Cylinder Regulator OPSO
UUCSR485TPHK	CSR485 Single Cylinder Regulator OPSO w/ Clessinox Stainless Steel 35kW 1.2m Outlet Hose 15&22mm Compression
UUCSR485SCK	CSR485 Single Cylinder Regulator OPSO Wall Mount Kit with Rubber Pigtail
UUCSR485DCS	CSR485 Single Cylinder Regulator OPSO Wall Mount Dual Cylinder Kit with Rubber Pigtails
UUCSR485MCO	CSR485 Single Cylinder Regulator OPSO Wall Mount Manual Changeover Kit with Rubber Pigtails

CSR OPSO RESET INSTRUCTIONS

